
stix2-slider Documentation

Release 1.0.0

OASIS Open

Jan 14, 2019

Contents:

1	Introduction	3
2	Installing	5
2.1	Requirements	5
2.2	Installation Steps	5
3	Command Line Interface	7
4	Mappings from STIX 1.x to STIX 2.x	9
4.1	Top Level Object Mappings	10
4.2	Common Properties	10
4.3	Attack Pattern	11
4.4	Campaigns	12
4.5	Course of Action	13
4.6	Indicator	14
4.7	Location	16
4.8	Malware	17
4.9	Report	18
4.10	Threat Actor	20
4.11	Tool	21
4.12	Vulnerability	22
5	Mappings from STIX 2.x to CybOX 2.x	25
6	Conversion Issues	27
6.1	Single vs. Multiple	27
6.2	Related-To Relationships	27
6.3	Data Markings	27
6.4	Kill Chains	27
6.5	Versioning	28
7	Warning Messages	29
7.1	General	29
7.2	Possible issue in original STIX 2.x content	29
7.3	Multiple values are not supported in STIX 1.x	30
7.4	Dropping Content not supported in STIX 1.x	30
7.5	STIX Slider currently doesn't process this content	31

7.6	STIX Slider conversion based on assumptions	31
8	Indices and tables	33

To convert STIX 1.x XML to STIX 2.x JSON use the [stix2-elevator](#).

CHAPTER 1

Introduction

The stix-slider is a software tool for ‘sliding’ STIX 2.x JSON to STIX 1.x XML. Due to the differences between STIX 1.x and STIX 2.x, this conversion is a best-effort only. During the conversion, stix-slider produces many warning messages about the assumptions it needs to make to produce valid STIX 1.x XML, and what information was not able to be converted.

It important to emphasize that the slider is not for use in a *production* system without human inspection of the results it produces. It should be used to explore how STIX 2.x content could potentially be represented in STIX 1.x. Using the current version of the slider will provide insight to issues that might need to be mitigated to convert your STIX 2.x content for use in application that accept only STIX 1.x content.

2.1 Requirements

- Python 2.7, or 3.3+
- `python-stix` and its dependencies

Note: Make sure to use either the latest version of `python-stix` 1.1.1.x or 1.2.0.x, depending on whether you want to support STIX 1.1.1 or STIX 1.2.

- `python-stix2` $\geq$ 1.1.0
- `stixmarx` $\geq$ 1.0.3
- `stix-validator` $\geq$ 2.5.0

2.2 Installation Steps

Install with pip:

```
$ pip install stix2-slider
```

This will install all necessary dependencies, including the latest version of `python-stix`.

If you need to support older STIX 1.1.1 content, install `python-stix` 1.1.1.x first:

```
$ pip install 'stix<1.2'
$ pip install stix2-slider
```

You can also install the `stix-slider` from GitHub to get the latest (unstable) version:

```
$ pip install git+https://github.com/oasis-open/cti-stix-slider.git
```

CHAPTER 3

Command Line Interface

The slider comes with a bundled script which you can use to convert STIX 2.x content to STIX 1.x content:

```
usage: stix2_slider [-h] [--no-squirrel-gaps] [--validator-args VALIDATOR_ARGS]
                  [-e ENABLE] [-d DISABLE] [-s]
                  [--message-log-directory MESSAGE_LOG_DIRECTORY]
                  [--log-level {DEBUG,INFO,WARN,ERROR,CRITICAL}]
                  [--use-namespace USE_NAMESPACE]
                  file

stix2-slider v2.0.0
```

The stix2-slider is a work-in-progress. It should be used to explore how existing STIX 2.x would potentially be represented in STIX 1.x. Using the current version of the stix2-slider will provide insight to issues that might need to be mitigated so you can use an application that supports only STIX 1.x content.

positional arguments:

```
file      The input STIX 2.x document to be 'slid' to STIX 1.x.
```

optional arguments:

```
-h, --help
    show this help message and exit

--no-squirrel-gaps
    Do not include STIX 2.x content that cannot be
    represented directly in STIX 1.x using the description
    property.

--validator-args VALIDATOR_ARGS
    Arguments to pass to stix-validator. Example:
    stix2_slider <file> --validator-args="--best-
    practices"
```

(continues on next page)

(continued from previous page)

```
-e ENABLE, --enable ENABLE
    A comma-separated list of the stix2-slider messages to
    enable. If the --disable option is not used, no other
    messages will be shown. Example: stix2_slider <file>
    --enable 250

-d DISABLE, --disable DISABLE
    A comma-separated list of the stix2-slider messages to
    disable. Example: stix2_slider <file> --disable
    212,220

-s, --silent
    If this flag is set. All stix2-slider messages will be
    disabled.

--message-log-directory MESSAGE_LOG_DIRECTORY
    If this flag is set, all stix2-slider messages will be
    saved to file. The name of the file will be the input
    file with extension .log in the specified directory.
    Note, make sure the directory already exists. Example:
    stix2_slider <file> --message-log-directory "../logs"

--log-level {DEBUG,INFO,WARN,ERROR,CRITICAL}
    The logging output level.

--use-namespace USE_NAMESPACE
    Override the 'example' namespace with provided one.
    The format is the prefix, namespace uri and optionally
    the schema location separated by a space. Example:
    stix2_slider <file> --use-namespace="example
    http://example.com"
```

Refer to the [Warning Messages](#) section for all stix2-slider messages. Use the associated code number to `--enable` or `--disable` a message. By default, the stix2-slider displays all messages.

Note: disabling the message does not disable any functionality.

It is recommended that you ensure that the input STIX 2.x file is valid before submitting it to the slider. Use the [stix2-validator](#).

Mappings from STIX 1.x to STIX 2.x

This section outlines the disposition of each property of the top-level objects when converted.

For each STIX 2.x object that was converted the following options are possible:

- **STIX 2.x property mapped directly to a STIX 1.x property.** This property's value is used unaltered in the conversion to 2.x.
- **STIX 2.x property translated into STIX 1.x property.** This property's value must undergo some minor processing to determine the corresponding content for 1.x.
- **STIX 2.x relationship mapped using STIX 1.x property.** This 2.x relationship object is used to construct an embedded STIX 1.x relationship. If the STIX 2.x `relationship-type` is not listed below, then that relationship will not be converted to an embedded STIX 1.x relationship. The “reverse” notation indicates the the STIX 1.x property is found on target object.
- **STIX 2.x property recorded in the STIX 1.x description property.** This 2.x property has no corresponding property in STIX 1.x, but its value can be (optionally) included in the description property of the 1.x object as text.

If the STIX 2.x content was created using the elevator it might be the case that it recorded some 1.x properties in the description. However, the slider makes no attempt to examine the content of the 2.x descriptor property to determine if it can use information found within it to populate the original 1.x properties.

- **STIX 2.x property not mapped.** This property will not be included in the converted 1.x object.

4.1 Top Level Object Mappings

STIX 2.x object	STIX 1.x object
attack-pattern	ttp:Attack_Pattern
bundle	Package
campaign	Campaign
course-of-action	Course_Of_Action
identity	Information_Source or ttp:Victim_Targeting
indicator	Indicator
intrusion-set	<i>not converted</i>
location	xpil:Address
malware	ttp:MalwareInstance
observed-data	Observable
report	Report
threat-actor	Threat Actor
tool	ttp:Tool
vulnerability	et:Vulnerability

4.2 Common Properties

STIX 2.x Properties Mapped Directly to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
created	<i>not converted</i> (see modified)
description	Description
modified	timestamp
name	Title

STIX 2.x Properties Translated to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
type	<i>implicitly defined by its element name or explicitly using xsi:type</i>
id	id
created_by_ref	Information_Source
external_references	Information_Source, et:Vulnerability.cve_id, ttp:Attack_Patterns.capec.id
object_markings_ref	Handling
granular_markings	Handling

STIX 2.x Relationships Mapped Using STIX 1.x Relationships

none

STIX 2.x Properties Recorded in the STIX 1.x Description Property

none

STIX 2.x Properties Not Mapped

- revoked

4.3 Attack Pattern

STIX 2.x Properties Mapped Directly to STIX 1.x Properties

none

STIX 2.x Properties Translated to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
external_references	capec_id
kill_chain_phases	ttp:Kill_Chain_Phases

STIX 2.x Relationships Mapped Using STIX 1.x Relationships

STIX 2.x relationship type	STIX 1.x property
targets (identity only)	ttp:Victim_Targeting
targets (vulnerability only)	ttp:Exploit_Targets
uses (malware, tool)	ttp:Related_TTPs

STIX 2.x Properties Recorded in the STIX 1.x Description Property

- labels

STIX 2.x Properties Not Mapped

none

An Example

STIX 2.x in JSON

```
{
  "type": "attack-pattern",
  "id": "attack-pattern--19da6e1c-71ab-4c2f-886d-d620d09d3b5a",
  "created": "2016-08-08T15:50:10.983Z",
  "modified": "2017-01-30T21:15:04.127Z",
  "external_references": [
    {
      "external_id": "CAPEC-148",
      "source_name": "capec",
      "url": "https://capec.mitre.org/data/definitions/148.html"
    }
  ],
  "name": "Content Spoofing"
}
```

STIX 1.x in XML

```
<stix:TTP id="example:ttp-19da6e1c-71ab-4c2f-886d-d620d09d3b5a" timestamp="2017-01-
→30T21:15:04.127000+00:00" xsi:type='ttp:TTPType'>
  <ttp:Behavior>
    <ttp:Attack_Patterns>
      <ttp:Attack_Pattern capec_id="CAPEC-148">
        <ttp:Title>Content Spoofing</ttp:Title>
      </ttp:Attack_Pattern>
    </ttp:Attack_Patterns>
  </ttp:Behavior>
```

(continues on next page)

(continued from previous page)

```

<ttp:Information_Source>
  <stixCommon:References>
    <stixCommon:Reference>SOURCE: capec - https://capec.mitre.org/data/
    definitions/148.html</stixCommon:Reference>
  </stixCommon:References>
</ttp:Information_Source>
</stix:TTP>

```

4.4 Campaigns

STIX 2.x Properties Mapped Directly to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
aliases	Names
objective	Intended_Effect

STIX 2.x Properties Translated to STIX 1.x Properties

none

STIX 2.x Relationships Mapped Using STIX 1.x Relationships

STIX 2.x relationship type	STIX 1.x property
uses	Related_TTPs
indicates (reverse)	Related_Indicators
attributed-to	Attribution
related-to (campaign)	Associated_Campaigns

STIX 2.x Properties Recorded in the STIX 1.x Description Property

- first_seen
- last_seen
- labels

STIX 2.x Properties Not Mapped

none

An Example

STIX 2.x in JSON

```

{
  "created": "2014-08-08T15:50:10.983Z",
  "description": "Attacking ATM machines in the Eastern US",
  "external_references": [
    {
      "source_name": "ACME",
      "url": "http://foo.com/bar"
    },
    {
      "source_name": "wikipedia",
      "url": "https://en.wikipedia.org/wiki/Automated_teller_machine"
    }
  ]
}

```

(continues on next page)

(continued from previous page)

```

    },
    {
      "source_name": "ACME Bugzilla",
      "external_id": "1370",
      "url": "https://www.example.com/bugs/1370"
    }
  ],
  "id": "campaign--e5268b6e-4931-42f1-b379-87f48eb41b1e",
  "modified": "2014-08-08T15:50:10.983Z",
  "name": "Compromise of ATM Machines",
  "type": "campaign"
}

```

STIX 1.x in XML

```

<stix:Campaign id="example:campaign-e5268b6e-4931-42f1-b379-87f48eb41b1e" timestamp=
→ "2014-08-08T15:50:10.983000+00:00" xsi:type='campaign:CampaignType'>
  <campaign:Title>Compromise of ATM Machines</campaign:Title>
  <campaign:Description>Attacking ATM machines in the Eastern US</
→ campaign:Description>
  <campaign:Information_Source>
    <stixCommon:References>
      <stixCommon:Reference>SOURCE: ACME - http://foo.com/bar</
→ stixCommon:Reference>
      <stixCommon:Reference>SOURCE: wikipedia - https://en.wikipedia.org/
→ wiki/Automated_teller_machine</stixCommon:Reference>
      <stixCommon:Reference>SOURCE: ACME Bugzilla - https://www.example.com/
→ bugs/1370</stixCommon:Reference>
      <stixCommon:Reference>SOURCE: ACME Bugzilla - EXTERNAL ID: 1370</
→ stixCommon:Reference>
    </stixCommon:References>
  </campaign:Information_Source>
</stix:Campaign>

```

4.5 Course of Action

In STIX 2.x the course-of-action object is defined as a stub. This means that in STIX 2.x this object type is pretty “bare-bones”, not containing most of the properties that were found in STIX 1.x.

STIX 2.x Properties Mapped Directly to STIX 1.x Properties

none

STIX 2.x Properties Translated to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
labels	Type

STIX 2.x Relationships Mapped Using STIX 1.x Relationships

STIX 2.x relationship type	STIX 1.x property
related-to (course-of-action)	Related_COAs

STIX 2.x Properties Recorded in the STIX 1.x Description Property

none

STIX Properties Not Mapped

none

An Example

STIX 2.x in JSON

```
{
  "created": "2017-01-27T13:49:41.298Z",
  "description": "\n\nSTAGE:\n\tResponse\n\nOBJECTIVE: Block communication
↪ between the PIVY agents and the C2 Server\n\nCONFIDENCE: High\n\nIMPACT:LowThis IP
↪ address is not used for legitimate hosting so there should be no operational impact.
↪ \n\nCOST:Low\n\nEFFICACY:High",
  "id": "course-of-action--495c9b28-b5d8-11e3-b7bb-000c29789db9",
  "labels": [
    "perimeter-blocking"
  ],
  "modified": "2017-01-27T13:49:41.298Z",
  "name": "Block traffic to PIVY C2 Server (10.10.10.10)",
  "type": "course-of-action"
}
```

STIX 1.x in XML

```
<stix:Course_Of_Action id="example:course-of-action-495c9b28-b5d8-11e3-b7bb-
↪ 000c29789db9" timestamp="2017-01-27T13:49:41.298000+00:00" xsi:type=
↪ 'coa:CourseOfActionType'>
  <coa:Title>Block traffic to PIVY C2 Server (10.10.10.10)</coa:Title>
  <coa:Type xsi:type="stixVocabs:CourseOfActionTypeVocab-1.0">Perimeter
↪ Blocking</coa:Type>
  <coa:Description>
    STAGE:
      Response
    OBJECTIVE: Block communication between the PIVY agents and the C2
↪ Server
    CONFIDENCE: High
    IMPACT:LowThis IP address is not used for legitimate hosting so there
↪ should be no operational impact.
    COST:Low
    EFFICACY:High
  </coa:Description>
</stix:Course_Of_Action>
```

Notice that although there is information in the STIX 2.x description property (from a previous use of the elevator) that could be used to populate STIX 1.x properties, the description property is transferred directly, with no additional processing.

4.6 Indicator

STIX 2.x Properties Mapped Directly to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
valid_from,valid_until	Valid_Time_Position
created_by_ref	Producer

STIX 2.x Properties Translated to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
kill_chain_phases	Kill_Chain_Phases
pattern	IndicatorExpression
labels	Type

STIX 2.x Relationships Mapped Using STIX 1.x Relationships

STIX 2.x relationship type	STIX 1.x property
detects	Indicated_TTP
indicates (campaign)	Related_Campaigns
indicates (attack-pattern, malware, tool)	Indicated_TTPs
related-to (indicator)	Related_Indicators

STIX 2.x Properties Recorded in the STIX 1.x Description Property

none

STIX 2.x Properties Not Mapped

none

An Example

STIX 2.x in JSON

```
{
  "created": "2014-05-08T09:00:00.000Z",
  "id": "indicator--53fe3b22-0201-47cf-85d0-97c02164528d",
  "labels": [
    "ip-watchlist"
  ],
  "modified": "2014-05-08T09:00:00.000Z",
  "name": "IP Address for known C2 channel",
  "pattern": "[ipv4-addr:value = '10.0.0.0']",
  "type": "indicator",
  "valid_from": "2014-05-08T09:00:00.000000Z"
}

{
  "created": "2014-05-08T09:00:00.000Z",
  "id": "relationship--9606dac3-965a-47d3-b270-8b17431ba0e4",
  "modified": "2014-05-08T09:00:00.000Z",
  "relationship_type": "indicates",
  "source_ref": "indicator--53fe3b22-0201-47cf-85d0-97c02164528d",
  "target_ref": "malware--73fe3b22-0201-47cf-85d0-97c02164528d",
  "type": "relationship"
}
```

STIX 1.x in XML

```
<stix:Indicator id="example:indicator-53fe3b22-0201-47cf-85d0-97c02164528d" timestamp=
↪ "2014-05-08T09:00:00:00:00" xsi:type='indicator:IndicatorType'>
  <indicator:Title>IP Address for known C2 channel</indicator:Title>
  <indicator:Type xsi:type="stixVocabs:IndicatorTypeVocab-1.1">IP Watchlist</
↪ indicator:Type>
```

(continues on next page)

(continued from previous page)

```

    <indicator:Valid_Time_Position>
      <indicator:Start_Time precision="second">2014-05-08T09:00:00+00:00</
↪indicator:Start_Time>
    </indicator:Valid_Time_Position>
    <indicator:Observable id="example:Observable-9f9e8592-1a3a-42f0-8e16-
↪56c062671a5c">
      <cybox:Object id="example:Address-3923ec77-e675-4db7-b2bb-8c42717b2b3a">
        <cybox:Properties xsi:type="AddressObj:AddressObjectType" category=
↪"ipv4-addr">
          <AddressObj:Address_Value condition="Equals">10.0.0.0</
↪AddressObj:Address_Value>
        </cybox:Properties>
      </cybox:Object>
    </indicator:Observable>
    <indicator:Indicated_TTP>
      <stixCommon:TTP idref="example:ttp-73fe3b22-0201-47cf-85d0-97c02164528d"
↪xsi:type='ttp:TTPType' />
    </indicator:Indicated_TTP>
  </stix:Indicator>

```

4.7 Location

STIX 2.x Properties Mapped Directly to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
administrative_area	administrative_area
country	country

STIX 2.x Properties Translated to STIX 1.x Properties

none

STIX 2.x Relationships Mapped Using STIX 1.x Relationships

STIX 2.x relationship type	STIX 1.x property
located-at (identity)	Addresses
located-at (threat-actor)	Identity/Addresses

STIX 2.x Properties Recorded in the STIX 1.x free_text_address Property

- latitude
- longitude
- precision
- region
- city
- code
- postal_code

STIX 2.x Properties Not Mapped

*none***An Example**

STIX 2.x in JSON

```
{
  "administrative_area": "California",
  "country": "US",
  "created": "2014-11-19T23:39:03.893Z",
  "id": "location--c1445467-fd92-4532-9161-1c3024ab6467",
  "modified": "2014-11-19T23:39:03.893Z",
  "spec_version": "2.1",
  "type": "location"
}
```

STIX 1.x in XML

```
<xpil:Address>
  <xal:Country xmlns:xal="urn:oasis:names:tc:ciq:xal:3">
    <xal:NameElement>US</xal:NameElement>
  </xal:Country>
  <xal:AdministrativeArea xmlns:xal="urn:oasis:names:tc:ciq:xal:3">
    <xal:NameElement>California</xal:NameElement>
  </xal:AdministrativeArea>
</xpil:Address>
```

4.8 Malware

The Malware object in STIX 2.x is a stub.

STIX 2.x Properties Mapped Directly to STIX 1.x Properties*none***STIX 2.x Properties Translated to STIX 1.x Properties**

STIX 2.x property	STIX 1.x property
kill_chain_phases	ttp:Kill_Chain_Phases
labels	Type

STIX 2.x Relationships Mapped Using STIX 1.x Relationships

STIX 2.x relationship type	STIX 1.x property
variant-of	ttp:Related_TTPs
uses	ttp:Related_TTPs
targets (vulnerability only)	ttp:Exploit_Targets
targets (identity only)	ttp:Victim_Targeting

STIX 2.x Properties Recorded in the STIX 1.x Description Property*none***STIX 2.x Properties Not Mapped***none*

An Example

STIX 2.x in JSON

```
{
  "created": "2017-01-27T13:49:53.997Z",
  "description": "Poison Ivy Trojan",
  "id": "malware--fdd60b30-b67c-11e3-b0b9-f01faf20d111",
  "labels": [
    "remote-access-trojan"
  ],
  "modified": "2017-01-27T13:49:53.997Z",
  "name": "Poison Ivy",
  "type": "malware"
}
```

STIX 1.x in XML

```
<stix:TTPs>
  <stix:TTP id="example:ttp-fdd60b30-b67c-11e3-b0b9-f01faf20d111" timestamp="2017-
↪01-27T13:49:53.997000+00:00" xsi:type='ttp:TTPType'>
    <ttp:Behavior>
      <ttp:Malware>
        <ttp:Malware_Instance>
          <ttp:Type xsi:type="stixVocabs:MalwareTypeVocab-1.0">Remote_
↪Access Trojan</ttp:Type>
          <ttp:Name>Poison Ivy</ttp:Name>
          <ttp:Description>Poison Ivy Trojan</ttp:Description>
        </ttp:Malware_Instance>
      </ttp:Malware>
    </ttp:Behavior>
  </stix:TTP>
</stix:TTPs>
```

4.9 Report

The Report object in 2.x does not contain objects, but only object references to STIX objects that are specified elsewhere (the location of the actual objects may not be contained in the same bundle that contains the report object). 1.x objects with only the `idref` property are created for each object reference in the STIX 2.x report.

STIX 2.x Properties Mapped Directly to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
name	Header.Title
description	Header.Description

STIX 2.x Properties Translated to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
object_refs (observed-data)	Observables
object_refs (indicator)	Indicators
object_refs (attack-pattern, malware, tool)	TTPs
object_refs (vulnerability)	Exploit_Targets
object_refs (course-of-action)	Courses_Of_Action
object_refs (campaign)	Campaigns
object_refs (threat-actor)	Threat_Actors
object_refs (identity, intrusion-set, relationship)	<i>not converted</i>
labels	Header.Intent

****STIX 2.x Properties Mapped Using STIX 1.x Relationships****

none

STIX 2.x Properties Recorded in the STIX 1.x Description Property

- published

STIX 2.x Properties Not Mapped

none

An Example

STIX 2.x in JSON

```
{
  "created": "2015-05-07T14:22:14.760Z",
  "created_by_ref": "identity--c1b58a86-e037-4069-814d-dd0bc75539e3",
  "description": "Adversary Alpha has a campaign against the ICS sector!",
  "id": "report--ab11f431-4b3b-457c-835f-59920625fe65",
  "labels": [
    "campaign-characterization"
  ],
  "modified": "2015-05-07T14:22:14.760Z",
  "name": "Report on Adversary Alpha's Campaign against the Industrial Control
↪Sector",
  "object_refs": [
    "campaign--1855cb8a-d96c-4859-a450-abb1e7c061f2",
    "indicator--66647c79-5766-4ca7-ab8a-a579056e3c83"
  ],
  "published": "2015-05-31T00:00:00.000Z",
  "type": "report"
}
```

STIX 1.x in XML

```
<stix:Report timestamp="2015-05-07T14:22:14.760000+00:00" id="example:report-ab11f431-
↪4b3b-457c-835f-59920625fe65" xsi:type='report:ReportType' version="1.0">
  <report:Header>
    <report:Title>Report on Adversary Alpha's Campaign against the Industrial
↪Control Sector</report:Title>
    <report:Intent xsi:type="stixVocabs:ReportIntentVocab-1.0">Campaign
↪Characterization</report:Intent>
    <report:Description ordinality="1">Adversary Alpha has a campaign against
↪the ICS sector!
    <report:Description ordinality="2">published: 2015-05-31 00:00:00+00:00</
↪report:Description>
```

(continues on next page)

(continued from previous page)

```

</report:Header>
<report:Campaigns>
  <report:Campaign idref="example:campaign-1855cb8a-d96c-4859-a450-
↪abbe7c061f2" xsi:type='campaign:CampaignType' />
</report:Campaigns>
<report:Indicators>
  <report:Indicator idref="example:indicator-66647c79-5766-4ca7-ab8a-
↪a579056e3c83" xsi:type='indicator:IndicatorType' />
</report:Indicators>
</stix:Report>

```

4.10 Threat Actor

STIX 2.x Properties Mapped Directly to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
goals	Intended_Effects

STIX 2.x Properties Translated to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
primary_motivation secondary_motivations personal_motivations	Motivation
sophistication	Sophistication
labels	Type

STIX 2.x Relationships Mapped Using STIX 1.x Relationships

STIX 2.x relationship type	STIX 1.x property
uses	Observed_TTPs
attributed-to (reverse)	Associated_Campaigns
related-to (threat-actor)	Associated_Actors

STIX 2.x Properties Recorded in the STIX 1.x Description Property

- name
- aliases
- roles
- resource_level

STIX 2.x Properties Not Mapped

none

An Example

STIX 2.x in JSON

```

{
  "created": "2017-01-27T13:49:54.326Z",
  "id": "threat-actor--9a8a0d25-7636-429b-a99e-b2a73cd0f11f",

```

(continues on next page)

(continued from previous page)

```

    "labels": [
      "nation-state"
    ],
    "modified": "2017-01-27T13:49:54.326Z",
    "name": "Adversary Bravo",
    "sophistication": "advanced",
    "type": "threat-actor"
  }

```

STIX 1.x in XML

```

<stix:Threat_Actor id="example:threat-actor-9a8a0d25-7636-429b-a99e-b2a73cd0f11f"
  timestamp="2017-01-27T13:49:54.326000+00:00"
  xsi:type='ta:ThreatActorType'>
  <ta:Title>Adversary Bravo</ta:Title>
  <ta:Type timestamp="2018-05-06T16:57:09.692723+00:00">
    <stixCommon:Value>State Actor / Agency</stixCommon:Value>
  </ta:Type>
  <ta:Sophistication timestamp="2018-05-06T16:57:09.692815+00:00">
    <stixCommon:Value>Expert</stixCommon:Value>
  </ta:Sophistication>
</stix:Threat_Actor>

```

4.11 Tool

STIX 2.x Properties Mapped Directly to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
name	Name (from CybOX)
labels	Type (from CybOX)
description	Description (from CybOX)
tool_version	Version (from CybOX)

STIX 2.x Properties Translated to STIX 2.x Properties

STIX 1.x property	STIX 1.x property
external_references	References (from CybOX)
kill_chain_phases	ttp:Kill_Chain_Phases

STIX 2.x Relationships Mapped Using STIX 1.x Relationships

STIX 2.x relationship type	STIX 1.x property
uses (attack-pattern) (reverse)	ttp:Related_TTPs
targets (identity)	ttp:Related_TTPs

STIX 2.x Properties Recorded in the STIX 1.x Description Property

- ttp:Intended_Effect

STIX 1.x Properties Not Mapped

- labels

An Example

STIX 2.x in JSON

```
{
  "type": "tool",
  "id": "tool--ce45f721-af14-4fc0-938c-000c16186418",
  "created": "2015-05-15T09:00:00.000Z",
  "modified": "2015-05-15T09:00:00.000Z",
  "name": "cachedump",
  "labels": [
    "credential-exploitation"
  ],
  "description": "This program extracts cached password hashes from a system's_
↪registry.",
  "kill_chain_phases": [
    {
      "kill_chain_name": "mandiant-attack-lifecycle-model",
      "phase_name": "escalate-privileges"
    }
  ]
}
```

STIX 1.x in XML

```
<stix:TTP id="example:tool-ce45f721-af14-4fc0-938c-000c16186418" timestamp="2015-05-
↪15T09:00:00:00" xsi:type='ttp:TTPType'>
  <ttp:Resources>
    <ttp:Tools>
      <ttp:Tool>
        <cyboxCommon:Description>This program extracts cached password_
↪hashes from a system's registry.</cyboxCommon:Description>
        <stixCommon:Title>cachedump</stixCommon:Title>
      </ttp:Tool>
    </ttp:Tools>
  </ttp:Resources>
  <ttp:Kill_Chain_Phases>
    <stixCommon:Kill_Chain_Phase name="escalate-privileges"
                                phase_id="example:TTP-17715bcf-84b9-4714-
↪a3cd-ffaf7fce9d10"
                                kill_chain_name="mandiant-attack-lifecycle-
↪model"
                                kill_chain_id="example:TTP-9df538ea-f0f0-
↪4cf0-a147-1397e51f0a63"/>
  </ttp:Kill_Chain_Phases>
</stix:TTP>
```

4.12 Vulnerability

STIX 2.x Properties Mapped Directly to STIX 1.x Properties

none

STIX 2.x Properties Translated to STIX 1.x Properties

STIX 2.x property	STIX 1.x property
external_references (source_name: cve)	CVE_ID
external_references (source_name: OSVDB_ID)	Reference

STIX 2.x Relationships Mapped Using STIX 1.x Relationships

STIX 2.x relationship type	STIX 1.x property
mitigates (reverse)	et:Potential_COAs
related-to (when not used for versioning)	et:Related_Exploit_Targets

STIX 2.x Properties Recorded in the STIX 1.x Description Property

- labels

STIX 2.x Properties Not Mapped

none

An Example

STIX 2.x in JSON

```
{
  "created": "2014-06-20T15:16:56.986Z",
  "external_references": [
    {
      "external_id": "CVE-2013-3893",
      "source_name": "cve"
    }
  ],
  "id": "vulnerability--e77c1e36-5b43-4c5c-b8cb-7b36035f2b90",
  "modified": "2017-01-27T13:49:54.310Z",
  "name": "Heartbleed",
  "type": "vulnerability"
}
```

STIX 1.x in XML

```
<stix:Exploit_Targets>
  <stixCommon:Exploit_Target id="example:et-e77c1e36-5b43-4c5c-b8cb-7b36035f2b90"
    timestamp="2014-06-20T15:16:56.986650+00:00"
    xsi:type='et:ExploitTargetType' version="1.2">
    <et:Title>Heartbleed</et:Title>
    <et:Vulnerability>
      <et:CVE_ID>CVE-2013-3893</et:CVE_ID>
    </et:Vulnerability>
  </stixCommon:Exploit_Target>
</stix:Exploit_Targets>
```


CHAPTER 5

Mappings from STIX 2.x to CybOX 2.x

The following table associates the CybOX 2.x object types with their STIX 2.x cyber observable types. For each CybOX object the table also indicates if the slider is able to convert the cyber observable object to CybOX 2.x.

CybOX object types not listed have no corresponding STIX 2.x cyber observable type, and therefore are not converted by the slider.

STIX 2.x Cyber Observable Type	CybOX 2.x Type	Converted in version
artifact	Artifact	yes
autonomous-system	AutonomousSystem	yes
directory	File	yes
domain-name	DomainName	yes
email-addr	Address	yes
email-message	EmailMessage	yes
file	File	yes
file:archive-ext	ArchiveFile	yes
file:raster-image-ext	ImageFile	yes
file:ntfs-ext	WinFile	yes
file:pdf-ext	PDFFile	yes
file>window-pebinary-ext	WinExecutableFile	yes
ipv4-addr	Address	yes
ipv6-addr	Address	yes
mac-addr	Address	yes
mutex	Mutex	yes
network-traffic	NetworkConnection	yes
network-traffic:http-request-ext	NetworkConnection and HTTPClientRequest	yes
network-traffic:icmp-ext	NetworkConnection and ICMPv4Packet	yes
network-traffic:socket-ext	NetworkConnection and NetworkSocket	yes
network-traffic:tcp-ext	<i>none</i>	no
process	Process	yes
process:windows-process-ext	WinProcess	yes
process:windows-service-ext	WinService	yes

Table 1 – continued from previous page

STIX 2.x Cyber Observable Type	CybOX 2.x Type	Converted in version
software	Product	yes
url	URI	yes
user-account	UserAccount, WinUser, UnixUserAccount	yes
user-account:unix-account-ext	UnixUserAccount	yes
window-registry-key	WinRegistryKey	yes
x509-certificate	X509Certificate	yes
x509-certificate:x509-v3-extensions-type	X509Certificate and X509V3Extensions	yes

6.1 Single vs. Multiple

Some properties in STIX 2.x allowed for multiple values, but the corresponding property in STIX 1.x does not. In these cases, the first value is used and a warning message is output.

6.2 Related-To Relationships

It is assumed that all `related-to` relationship between the same type of object should be used to refer to self-referencing STIX 1.x relationships. For instance a `related-to` relationship between two `threat-actor` objects will be used to populate the STIX 1.x `AssociatedActors` property.

Other `related-to` relationships will be ignored and a warning message will be displayed.

6.3 Data Markings

The `stix-slider` currently supports object-level markings only. Granular markings are ignored and a warning message will be displayed. Since that is the highest level of data marking available in STIX 2.x, any object downgraded will contain embedded object-level markings in their STIX 1.X representation regardless of using the same marking definition in multiple places. Therefore, it can result in a verbose output compared to its 2.X counterpart. The marking-definition objects will be placed in the `STIX_Header` section of the document.

The supported marking types are: TLP, Statement and AIS.

6.4 Kill Chains

Kill chains and their phases in STIX 2.x are referred to by their names. There is no `id` associated with a kill chain phase. Additionally, kill chains are not defined within STIX 2.x content. The assumption is that if a kill chain

is known among those sharing content, the names will be sufficient to identify them consistently. According to the STIX 2.x specification, if the Lockheed Martin Cyber Kill Chain™ is used the `kill_chain_name` will be `lockheed-martin-cyber-kill-chain`.

Because kill chains need to be explicitly defined within the STIX 1.x content, each kill chain phase found in the STIX 2.x content will be used to partially construct a kill chain definition. For this reason, the resultant kill chain will only contain the kill chain phases used.

6.5 Versioning

Both STIX 1.x and STIX 2.x support the versioning of objects, but there is no attempt by the slider to explicitly maintain versioning information when converting to STIX 1.x.

All converted objects will be assumed to be the one and only version of an object. If more than one object is found with the same id, it will *not* be flagged as an error.

CHAPTER 7

Warning Messages

7.1 General

Message	Code	Level
Observable Expressions should not contain placeholders	201	Error
Both console and output log have disabled messages	202	Warn
silent option is not compatible with a policy	203	Warn
options not initialized	204	Warn

7.2 Possible issue in original STIX 2.x content

Message	Code	Level
No source object exists for <i>[id]</i> to add the relationship <i>[relationship]</i>	301	Warn
Unknown hash type <i>[hash_type]</i> used in <i>[id]</i>	302	Warn
<i>[property]</i> is not a legal property in the pattern of <i>[id]</i>	303	Warn
Unknown address type <i>[type]</i> used in <i>[id]</i>	304	Warn
ref type <i>[type]</i> in <i>[id]</i> is not known	305	Warn
<i>[cyber_observable_id]</i> is not an index found in <i>[id]</i>	306	Warn
No object <i>[id]</i> is found to add the reference to	307	Warn
<i>[id1]</i> is not in this bundle. Referenced from <i>[id2]</i>	308	Warn
<i>is_encrypted</i> in <i>[id]</i> is true, but no <i>encryption_algorithm</i> is given	309	Info
<i>is_encrypted</i> in <i>[id]</i> is false, but <i>encryption_algorithm</i> is given	310	Info
<i>is_encrypted</i> in <i>[id]</i> is true, but no <i>decryption_key</i> is given	311	Info
<i>is_encrypted</i> in <i>[id]</i> is false, but <i>decryption_key</i> is given	312	Info
The <i>[property1]</i> property in <i>[id]</i> should be ' <i>[boolean]</i> ' if the <i>[property2]</i> property is [not] present	313	Warn
Cannot convert <i>[id]</i> because it doesn't contain both a <i>source_ref</i> and a <i>target_ref</i>	314	Warn
No <i>[ref_property]</i> object exists for <i>[id]</i> in relationship <i>[rel-id]</i>	315	Warn
ref type <i>[type]</i> in <i>[id]</i> is not known	316	Warn

7.3 Multiple values are not supported in STIX 1.x

Message	Code	Level
<i>[type]</i> in STIX 2.x has multiple <i>[property]</i> , only one is allowed in STIX 1.x. Using first in list - <i>[value]</i> omitted	401	Warn
Only one dll can be represented in STIX 1.x for <i>[id]</i> , using first one - ignoring <i>[value]</i>	402	Warn

7.4 Dropping Content not supported in STIX 1.x

Message	Code	Level
The <i>[relationship]</i> relationship between <i>[id1]</i> and <i>[id2]</i> is not supported in STIX 1.x	501	Warn
Multiple File Extensions in <i>[id]</i> not supported yet	502	Warn
<i>[property]</i> not representable in a STIX 1.x <i>[type]</i> . Found in <i>[id]</i>	503	Warn
<i>[property]</i> not representable in a STIX 1.x <i>[type]</i> . Found in the pattern of <i>[id]</i>	504	Warn
<i>[op]</i> cannot be converted to a STIX 1.x operator in the pattern of <i>[id]</i>	505	Warn
account_type property of <i>[id]</i> in STIX 2.x is not directly represented as a property in STIX 1.x	506	Warn
Received Line <i>[line]</i> in <i>[id]</i> has a prefix that is not representable in STIX 1.x	507	Warn
Unable to convert STIX 2.x sighting <i>[id]</i> because it doesn't refer to an indicator	508	Warn
NO MESSAGE ASSIGNED	509	
Identity has no property to store external-references from <i>[id]</i>	510	Warn
pe_type SYS in <i>[id]</i> is valid in STIX 2.x, but not in STIX 1.x	511	Warn
pe_type <i>[pe_type]</i> in <i>[id]</i> is allowed in STIX 2.x, but not in STIX 1.x	512	Warn
<i>[property]</i> is an XML attribute of <i>[cybox object type]</i> in STIX 1.x, so the operator 'equals' is assumed in <i>[id]</i>	513	Warn
Order may not be maintained for pdfids in <i>[id]</i>	514	Warn
The groups property of unix-account-ext contains strings, but the STIX 1.x property expects integers in <i>[property]</i>	515	Warn
No file name provided for binary_ref of <i>[id]</i> , therefore it cannot be represented in the STIX 1.x Process object	516	Warn
Hashes of the binary_ref of <i>[id]</i> process cannot be represented in the STIX 1.x Process object	517	Warn
resolves_to_refs in <i>[id]</i> not representable in STIX 1.x	518	Warn
Multiple Network Traffic extensions in <i>[id]</i> not supported yet	519	Warn
The user_id property of <i>[id]</i> in STIX 2.x is only represented as a property in STIX 1.x on UnixUserAccount objects	520	Warn
The path property in <i>[id]</i> is the only directory property supportable in STIX 1.x. <i>[property]</i> is ignored	521	Warn
Nested Archive Files in <i>[id]</i> not handled yet	522	Warn
STIX 1.x can only store the body and headers of an email message in <i>[id]</i> independently	523	Warn
Cannot convert STIX 2.x content that contains intrusion-sets	524	Error
<i>[id]</i> is not explicitly a member of a STIX 1.x Report	525	Warn
<i>[id]</i> cannot be represented in STIX 1.x	526	Warn
Relationship between <i>[id]</i> and a location is not supported in STIX 1.x	527	Warn
Ignoring <i>[id]</i> , because a <i>[type]</i> cannot be represented in STIX 1.x	528	Warn

7.5 STIX Slider currently doesn't process this content

Message	Code	Level
The <i>[property]</i> property in <i>[id]</i> can refer to any object, so it is not handled yet.	601	Warn
number indicies in <i>[id]</i> not handled, yet	602	Warn
Unable to determine STIX 1.x type for <i>[id]</i>	603	Error
Granular Markings present in <i>[id]</i> are not supported by stix2slider	604	Warn
Source name <i>[name]</i> in external references of <i>[id]</i> not handled, yet	605	Warn
<i>[property]</i> property in <i>[id]</i> not handled yet	606	Warn
contains_refs in <i>[id]</i> not handled	607	Warn
protocols property in <i>[id]</i> not handled, yet	608	Warn
tcp-ext in <i>[id]</i> not handled, yet	609	Warn
Operator for <code>Artifact.Raw_Artifact</code> in <i>[id]</i> not handled yet	610	Warn
Nested extensions and references in patterns are not handled, yet. Found in pattern of <i>[id]</i>	611	Warn
<i>[ref_id]</i> in <i>[id]</i> cannot be represented in STIX 1.x	612	Warn

7.6 STIX Slider conversion based on assumptions

Message	Code	Level
Assuming <code>icmp</code> packet in <i>[id]</i> is v4	701	Info
<code>InformationSource</code> descriptions order or content in may not correspond to the references in <i>[id]</i>	702	Info
<i>[ref_id]</i> in <i>[id]</i> is not explicitly a member of a STIX 1.x report	703	Info

CHAPTER 8

Indices and tables

- `genindex`
- `modindex`
- `search`